



NEW FABRIC AND/OR CHEMICAL APPLICATION PROCESS

All companies submitting new fabrics and/or chemicals for California State Fire Marshal (CSFM) registration are required to follow the procedures outlined below. Failure to meet the requirements of these procedures will result in your application package being returned.

NEW FABRIC APPLICATIONS MUST INCLUDE:

- 1) Complete application <https://osfm.fire.ca.gov/media/3111/application-for-decorative-materials-fabric-registration.pdf>
(Include exact fiber content and total weight in ounces.)
- 2) Appropriate fee of \$200.00
- 3) Test report from a CSFM Approved Laboratory
- 4) Samples of material cut and labeled in the following manner:
 - a. 1 - 3 ½" x 10" treated sample cut on the Warp (parallel to the selvage)
 - b. 1 - 3 ½" x 10" treated sample cut on the Fill (perpendicular to the selvage)

ADDING FABRICS TO EXISTING REGISTRATION MUST INCLUDE:

Complete application <https://osfm.fire.ca.gov/media/3111/application-for-decorative-materials-fabric-registration.pdf>

- 1) (Include exact fiber content and total weight in ounces, fabrics being added to existing registration numbers cannot differ by more/less than 4 oz.)
- 2) Appropriate fee of \$50.00
- 3) Test report from a CSFM Approved Laboratory
Samples of material cut and labeled in the following manner:
 - a. 1 - 3 ½" x 10" treated sample cut on the Warp (parallel to the selvage)
 - b. 1 - 3 ½" x 10" treated sample cut on the Fill (perpendicular to the selvage)

NEW CHEMICAL APPLICATIONS MUST INCLUDE:

- 1) Complete application <https://osfm.fire.ca.gov/media/3110/application-for-decorative-materials-chemicals-registration.pdf>
 - 2) Appropriate fee of \$200.00
 - 3) Test report from a CSFM Approved Laboratory.
 - 4) Product Data Sheet/Manufacturer's Instructions
 - 5) Material Safety Data Sheet with PH noted
- State Fire Marshal Approved Laboratory <https://osfm.fire.ca.gov/divisions/fire-engineering-and-investigations/flame-retardant-chemicals-and-fabrics/>

NOTE: Testing shall be done using Title 19, California Code of Regulation. There will be no exceptions. For exterior use fabrics and/or chemicals, water extraction/leaching and accelerated weathering tests are required.